

TP9361 Intrinsically Safe

SPECIFICATIONS



Designed for maximum safety in the field and enhanced usability

Intrinsically Safe Tait DMR portables are engineered to operate safely in hazardous environments, ensuring your people have communications they can depend on while they get the job done.

Built Tait Tough, the flexible TP9361 portable offers conventional and trunked DMR operation as well as full MPT 1327, and analog conventional FM in one device.

Improve workforce safety with smart features such as Location Services, Tait GeoFencing, and Man Down functionality.



KEY FEATURES

- Intrinsically Safe portable designed to meet stringent International safety standards
- Future proof multi-mode portable (DMR Tier 2 and Tier 3, MPT 1327 and conventional analog FM)
- Provides choice and interoperability using open standard DMR protocol
- Supporting worker safety with man down alerts and built in GNSS positioning
- Internationally recognized color for intrinsic safety
- Built to last Tait Tough portables engineered for demanding environments with IP67 rating and exceeding MIL standard specification
- Complete package with accessories portfolio
- Data Services improve organizational efficiencies

TP9361 Intrinsically Safe

SPECIFICATIONS

FEATURES AND BENEFITS*

Flexible and Easy to Use

- Clear communication with DMR AMBE+2™ enhanced digital vocoder and digital noise suppression software
- Four programmable function keys and three-way selector
- Tailor your experience with wide range of accessory options
- Channel Authorization for DMR Tier 2 and Tier 3 gives users confidence their call will be heard
- Proceed to Talk Tone available in all modes, for consistent operation

DMR smart voice and data

Benefit from the spectral efficiency, multi-vendor interoperability, security, migration and data capability of DMR open standards

- Text messaging for enhanced and unambiguous communications
- Short data messages for location, status and text
- Packet data over traffic channels for work force management and customer specific applications
- IP data in digital trunked mode
- USBD Fast Polling – capable of 2000 polls per minute on compatible DMR Tier 3 systems

Tait Tough – Designed to perform

- Water-shedding grille maintains transmitted voice clarity and high audio volume in wet environments
- IP65 & IP67 dust and water proof
- Display screen protected by recess
- Drop test exceeds MIL-STD-810G
- Shock absorbing corner protection
- Supported by a range of Tait Tough audio and carry accessories

Complete package with accessories portfolio

- Intrinsically Safe audio accessories including speaker-microphones, headsets and earpieces.
- Intrinsically Safe Li-Ion battery.
- Intrinsically Safe compatible battery charger.

DMR specifications

Tait infrastructure and terminals are designed as per the following DMR Specifications:

- ETSI TR 102 398 V1.4.1 General System Design.
- ETSI TS 102 361-1 V2.5.1 DMR Air Interface (AI) protocol.
- ETSI TS 102 361-2 V2.4.1 DMR voice and generic services and facilities
- ETSI TS 102 361-3 V1.3.1 DMR data protocol.
- ETSI TS 102 361-4 V1.11.1 DMR trunking protocol

Extensive network capabilities

- Future proof quad mode portable radio offering Trunked DMR, Conventional DMR, MPT 1327 and analog conventional FM in one device
- Roaming between MPT 1327 and DMR Tier 3 trunked networks
- Roaming between Conventional FM and DMR Tier 2 Conventional networks
- Individual calls for private discussions
- A range of call types for individual and group communication with without the distraction of irrelevant traffic
- Increased channel capacity with up to 1,500 channels
- Scanning modes include: priority, dual priority, zone, and background scan – groups are editable
- PSTN dialling allows a user to make phone calls on DMR systems that support telephone interconnect
- Trunked operation allows for individual and private calls within designated groups
- Pre-set status messages

Internationally recognized IS color

The TP9361 IS model is made in the internationally recognized blue color for Intrinsically Safe portables, ensuring instant recognition in the field.

Improve workforce safety

- Programmable emergency key is easily accessible and highly visible
- Man Down and Lone Worker
- Integrated GNSS option for Location Services
- Tait GeoFencing option for automated location based behavior
- Emergency calls have priority access to trunked networks
- Blast Alarms and Audible Alerts in DMR modes
- Designed and tested to meet relevant global IS standards:
 - The battery circuitry is fully encapsulated
 - The radio circuit has a stored energy limitation, which prevents internal sparking or overheating in the unlikely event of a circuit failure
 - Component and conductor spacing and protective coatings prevent short circuits caused by dust or atmospheric contamination

Tait GeoFencing Automation

- Radios can automatically take a range of actions based on location, such as change modes, send messages, hazardous area alert, or activate lone worker features
- Independent of the network, dispatch, or any other software applications

Tait EnableFleet industry leading configuration management system

- Total visibility of your fleet from a secure, central point of control
- Wired connection or Over-the-air-programming (OTAP) to update configuration and software files
- OTAP via DMR trunked networks

Secure communications

- Radio inhibit and uninhibit to allow management of misplaced or stolen radios
- Configurable DMR authentication to protect network access
- Supports end-to-end encryption, including DES, ARC4, or AES
- Tait EnableProtect Advanced System Key ensures only authorized personnel can access radio software and configuration

TP9361 Intrinsically Safe

SPECIFICATIONS

GENERAL

Conventional Mode

| | |
|----------------|--------------------------------|
| Networks | 26 |
| Channels/zones | 1,500 channels / 100 zones |
| Scan groups | 300 with up to 50 members each |

Trunked Mode

| | |
|---|--|
| Networks | 4 |
| Talk groups | 512 talk group lists |
| Zones and work groups | 1,000 zones, 1,000 work groups |
| Frequency stability | ±0.5ppm (-22°F to 140°F / -30°C to 60°C) |
| Dimensions (DxWxH) - With Li-Ion 2300 mAh battery | 1.77 x 2.56 x 5.35in (45 x 65 x 136mm) excluding knobs |
| Weight - With Li-Ion 2300 mAh battery | 13.93oz (395g) – no antenna, 15.17oz (430g) with IS battery and antenna |
| Radio Operating temperature range | -20°C to 60°C (-4°F to 140°F) † |
| Water and dust protection | IP67 & IP65 |
| ESD rating | +/- 4kV contact discharge and +/-8kV air discharge |
| Frequency increment/channel step | 2.5/3.125/5/6.25kHz |
| Air interface standard | DMR: ETSI TS 102 361-1, -2, -3, -4 |
| General system design standard | ETSI TR 102 398 V14.1 |
| Signalling options (Analog) | MDC1200, encode and decode, Two tone decode, PL (CTCSS), DPL (DCS), Selcall (5 - tone) |
| Vocoder type | AMBE +2™ |
| Packet Data | ½ Rate, ¾ Rate, Full rate, Single Slot |

† Subject to Compliance, Ambient Temperature: T4 -20°C < Ta < +50°C, T3 -20°C < Ta < +60°C

| TRANSMITTER | VHF | UHF | 700/800MHZ |
|--|--------------------------------------|--------------------------------------|--------------------|
| Frequency range | 136-174 MHz (B1) 174-225 MHz (C0) | 380-470 MHz (HB) 450-520 MHz (H7) | 762-870 MHz (K5) |
| Output power | 5W, 3W, 2W, 1W | 4W, 2.5W, 2W, 1W | 2.5W, 2.5W, 2W, 1W |
| FM Transmit Deviation (12.5kHz / 25kHz channels) * | 2.5 / 5kHz | 2.5 / 5kHz | 2.5 / 5kHz |
| FM hum and noise (analog) | | | |
| 12.5kHz channel | -40dB | -40dB | -40dB |
| 25kHz channel [†] | -45dB | -45dB | -45dB |
| Conducted/radiated emissions | -36dBm <1GHz, -30dBm >1GHz | -36dBm <1GHz, -30dBm >1GHz | -20dBm |
| Audio response | +1/-3dB | +1/-3dB | +1/-3dB |
| Audio distortion (Analog) | 2.5% | 2.5% | 2.5% |

| RECEIVER | VHF | UHF | 700/800MHZ |
|--|-------------------------------------|--------------------------------------|------------------------------|
| Frequency range | 136-174MHz (B1) 174-225 MHz (C0) | 380-470 MHz (HB) 450-520 MHz (H7) | 762-776 & 850-870 MHz (K5) |
| Channel Spacing * | 6.25/12.5/25kHz | 6.25/12.5/25kHz | 6.25/12.5/25kHz |
| Sensitivity (typical) | | | |
| Analog (12dB SINAD) | -120dBm(0.22µV) | -120dBm (0.22µV) | -120dBm (0.22µV) |
| DMR (1% BER (ETSS300-113)) | -119dBm (0.25µV) | -119dBm (0.25µV) | -119dBm (0.25µV) |
| DMR (5% BER) | -123dBm (0.16µV) | -123dBm (0.16µV) | -123dBm (0.16µV) |
| Intermodulation rejection (TIA603E) | 75dB | 75dB | 75dB |
| Intermodulation rejection (ETS 300) | 65dB | 65dB | 65dB |
| Selectivity (Analog) | | | |
| TIA603E (2 Tone) | 12.5kHz: 50dB 25kHz: 70dB | 12.5kHz: 50dB 25kHz: 70dB | 12.5kHz: 50dB 25kHz: 70dB |
| ETS 3000-086 & TIA603E 1 Tone | 12.5kHz: 52dB 25kHz: 73dB | 12.5kHz: 50dB 25kHz: 70dB | 12.5kHz: 60dB 25kHz: 70dB |
| FM hum and noise (Narrowband / Wideband) | -40dB / -45dB | -40dB / -45dB | -40dB / -45dB |
| Spurious Rejection (TIA603E) | 70dB | 70dB | 70dB |
| Conducted Emissions (TIA603E) | 70dB | 70dB | 70dB |
| Rated Audio (Internal) | 0.5W | 0.5W | 0.5W |
| Audio Response (TIA603E) | +1/-3dB | +1/-3dB | +1/-3dB |
| Audio Distortion (Rated audio) | 2% | 2% | 2% |

* Wideband operation subject to FCC regulations

[†]Wideband operation is not available in the USA in some bands

CHARGER AND BATTERY

| | |
|---|--|
| Charger options (Li-Ion) | IS compatible desktop and vehicle chargers |
| Battery shift life (DMR mode, standard config) | Li-Ion 2300 mAh 15 hours (5/5/90)* |
| Battery shift life (Analog mode, standard config) | Li-Ion 2300 mAh 11.5 hours (5/5/90)* |

* Battery performance is dependent on frequency, temperature, and operational configuration.

TP9361 Intrinsically Safe

SPECIFICATIONS



MILITARY STANDARDS 810C, D, E, F AND G

| Applicable MIL-STD | Method | Procedure | Applicable MIL-STD | Method | Procedure |
|--------------------|--------|-----------|--------------------|--------|-----------|
| Low pressure | 500.5 | 2 | Humidity | 507.5 | 2 |
| High temperature | 501.5 | 1,2 | Salt fog | 509.5 | 1 |
| Low temperature | 502.5 | 1,2 | Sand & Dust | 510.5 | 1, 2 |
| Temperature shock | 503.5 | 1 | Immersion | 512.5 | 1 |
| Solar radiation | 505.5 | 1 | Vibration | 514.6 | 1 |
| Rain | 506.5 | 1,3 | Shock | 516.5 | 1,4,5,6 |

REGULATORY DATA

| | USA (FCC) | CANADA (ISED) | EUROPE/UK (CE) | AUSTRALIA/NEW ZEALAND (AS/NZ) |
|------------------|-----------|---------------|----------------|-------------------------------|
| VHF (136-174MHz) | ✓ | ✓ | ✓ | ✓ |
| UHF (320-380MHz) | - | - | ✓ | - |
| UHF (380-470MHz) | ✓ | ✓ | ✓ | ✓ |
| UHF (450-520MHz) | ✓ | - | - | ✓ |
| 800 MHz | ✓ | ✓ | - | - |

IS COMPLIANCE * OUTPUT POWER

| IS COMPLIANCE * | OUTPUT POWER | USA | CANADA | EUROPE/UK | AUSTRALIA/NZ |
|------------------|--------------|--|---|-----------------------------|----------------------|
| VHF (136-174MHz) | 1-5 W | Class I Zone 1, AEx ib IIA T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | Ex ib IIA T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | II 2 G Ex ib IIA T4...T3 Gb | Ex ib IIA T4...T3 Gb |
| | 1 W | Class I Zone 1, AEx ib IIC T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | Ex ib IIC T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | II 2 G Ex ib IIC T4...T3 Gb | Ex ib IIC T4...T3 Gb |
| UHF (320-380MHz) | 1-4 W | | | II 2 G Ex ib IIA T4...T3 Gb | |
| | 1 W | | | II 2 G Ex ib IIC T4...T3 Gb | |
| UHF (380-470MHz) | 1-4 W | Class I Zone 1, AEx ib IIA T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | Ex ib IIA T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | II 2 G Ex ib IIA T4...T3 Gb | Ex ib IIA T4...T3 Gb |
| | 1 W | Class I Zone 1, AEx ib IIC T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | Ex ib IIC T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | II 2 G Ex ib IIC T4...T3 Gb | Ex ib IIC T4...T3 Gb |
| UHF (450-520MHz) | 1-4 W | Class I Zone 1, AEx ib IIA T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | | | Ex ib IIA T4...T3 Gb |
| | 1 W | Class I Zone 1, AEx ib IIC T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | | | Ex ib IIC T4...T3 Gb |
| 800MHz | 1-2.5 W | Class I Zone 1, AEx ib IIA T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | Ex ib IIA T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | | Ex ib IIA T4...T3 Gb |
| | 1 W | Class I Zone 1, AEx ib IIC T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | Ex ib IIC T4...T3 Gb Class I Div 2, Group A, B, C, D Class II, Div 2, Group E, F, G Class III, Div 1 | | Ex ib IIC T4...T3 Gb |

TAIT DMR SOLUTION

Backed up by our proven radio network expertise, the TP9361 is part of our larger DMR offering. The Tait DMR solution consists of terminals, infrastructure, applications, services and integration with third party interfaces to ensure that your organization can reap all the benefits of the spectrally-efficient DMR standard in a mission critical environment.

Tait has taken every care in compiling this specification sheet, but we're always innovating and therefore changes to our models, designs, technical specification, visuals and other information included in this specification sheet could occur. For the most up-to-date information and for a copy of our terms and conditions please visit our website www.taitcommunications.com or check with your nearest Tait office or authorized dealer.

The words "Tait", "TAIT AXIOM", "Tait Unified", and the "Tait" logo are trademarks of Tait International Limited. Tait International Limited facilities are certified for ISO 9001:2015 (Quality Management System), ISO 14001:2015 (Environmental Management System) and ISO 45001:2018 (Occupational Health and Safety Management System) for aspects associated with the design, manufacture and distribution of radio communications and control equipment, systems and services. In addition, all our Regional Head Offices are certified to ISO 9001.

